


Movement by Perfection



The Royal League in **ventilation**, control and drive technology



Product documentation

Type
FN050-4EK.4I.V7P1

Article number
140057

Product documentation

Customer

Beijing Hengrui Mechanical and Electrical Equipment
Co,Ltd

Project


+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

Type

FN050-4EK.4I.V7P1

Article number

140057



Contents

1.	Rubriküberschrift1 (CB_AF_Headline1)	Erro! Indicador não definido.
----	--------------------------------------	-------------------------------


1. Product specification

Technical data


Article number	140057
Type	FN050-4EK.4I.V7P1
Designation	Axial fan with sickle blades
Rated values	1~230V±10% 50Hz P ₁ 0,76kW 3.30A ΔI=5% 1230/min 16.0uF/400V 70°C 1~230V±10% 60Hz P ₁ 1,05kW 4,60A ΔI=0% 1250/min 16,0uF/400V 50°C
Electrical connection	Terminal box K62
Min. operating temperature °C	-25
Mounting type terminal box	Mounted on Stator
Type of protection	IP54
Thermal class	THCL155
Connection diagram	1360-104XA
Rating plate	1x fixed
Fitting position	H/Vu/Vo
Motor protection	thermal contact
Impregnation	Moisture and hot climate protection
Quality of bearings	ball bearing with long-time lubrication
Material Rotor	Aluminium
Painting rotor	unpainted
Material blades	Aluminium
Painting impeller	unpainted
Guard grille type	ring grill
Other	Balancing quality G 4,0
Painting mot.suspens	Motor suspension powder-coated consistency class 2
colour suspension	RAL 9005 (jet black)
Weight kg	13,30
ErP Data	Efficiency η_{statA} : 28,9 % Efficiency: $N_{actual} = 36,3 / N_{target} = 36^*$ *ErP 2013Does not comply with the stipulations of the ErP regulations

2. Characteristic Curve


Air performance




Acoustics



Power input



Efficiency



measured in full bell mouth without guard grille in installation type A according to ISO 5801

Please note: It's not allowed to use this fan in the stall area!*

*In doubt please ask your responsible ZIEHL-ABEGG sales contact.

Article number
140057

The Royal League

Die Königsklasse

Data of operating point	
frequency (f _{BP})	60
mains supply	1~ 230V 60Hz
guard grille	no




4. Connection diagram

1360-104XA

1~Motor with capacitor and thermostatic switch (if built in).

U1 brown
U2 blue
Z1 black
Z2 orange
TB white

Clockwise rotation



5. EU-Declaration of conformity



The Royal League in ventilation, **control** and drive technology

Intelligent control technology for any application

ZIEHL-ABEGG system capabilities:
Everything from a single source – perfectly matched for optimal performance

Please contact us. We would be pleased to design an individual solution for your requirements.

We would like to welcome you on our worldwide exhibitions. Please find our next exhibitions [here](#).