

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guard grille

Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
Phone +86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

Nominal data

Type	W3G710-NU31-03	
Motor	M3G150-IF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1680
Power consumption	W	3800
Current draw	A	5.8
Max. back pressure	Pa	420
Max. back pressure	in. wg	1.69
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	52.2	37.2	09 Power consumption P_{ed}	kW	3.68
02 Measurement category	A			09 Air flow q_v	m³/h	17375
03 Efficiency category	Static			09 Pressure increase p_{fs}	Pa	381
04 Efficiency grade N	55		40	10 Speed (rpm) n	min ⁻¹	1680
05 Variable speed drive	Yes			11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_s / 100\,000\text{ Pa}$ LU-205651

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Technical description

Weight	39.8 kg
Size	710 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Impeller material	PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Blade pitch	0°
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	≤ 3.5 mA
Electrical hookup	Terminal box

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guard grille


Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; CE; UKCA
Approval	EAC; UL 1004-7 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Product drawing




1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
3	Tightening torque 1.5 ± 0.2 Nm

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guard grille

Mounting dimensions



Diameter of the necessary recess for mounting the fan housing in the end device

BG630: D = Ø785 mm

BG710: D = Ø830 mm

BG800: D = Ø950 mm


BG910: D = Ø1050 mm

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guard grille

Terminal/plug assignment


configurable option				configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification																								
CON2	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV			D158 [0]	switch: set value	D101 [...]	source: sensor value	D147 [...]	D104 [...]	D12E [...]	D148 [...]	D16C [...]	D16A [...]	signal: tach out	(selected directly via IO mode)	OUTPUT	D130 [10]	signal: fan modulation level %	D130 [0]	D130 [11]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse input for auto-addressing	D130 [1]
			not active: pin open or applied voltage < 1.5VDC			D158 [2]	switch: fan enable / disable	D158 [5]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
			RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV			D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
			Umax = 50VDC, Imax = 20mA, SELV			D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
IO1	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV			D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]
			not active: pin open or applied voltage < 1.5VDC			D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
			RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV			D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
			RI = 125R, characteristic curve parameterizable, SELV			D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing										
IO2	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV			D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %	signal: remote control output 0-10V	pulse input for auto-addressing													
			RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %	signal: remote control output 0-10V	pulse input for auto-addressing													
			RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %	signal: remote control output 0-10V	pulse input for auto-addressing													
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
IO3	configurable IO mode	digital input	active: applied voltage 3.5-50VDC, SELV	D158 [0]	switch: set value	D158 [2]	source: sensor value	D158 [5]	D158 [6]	switch: control function: heating (pos.) / cooling (neg.)	D158 [6]	switch: parameter set: #1 / #2	D158 [6]	switch: tach out	(selected directly via IO mode)	INPUT	D159 [0]	switch: fan enable / disable	D159 [2]	D159 [3]	D15A [0]	D15A [1]	D15A [7]	D15A [8]	D15A [4]	D15A [5]	D15A [6]	D16E [...]		
			not active: pin open or applied voltage < 1.5VDC	D159 [0]	switch: fan enable / disable	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level high	D159 [0]	switch: set value source	D159 [2]	switch: control function: heating (pos.) / cooling (neg.)	D159 [3]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level %		signal: remote control output 0-10V	pulse input for auto-addressing												
			PWMIn3: digital input, idle level low	D15A [0]	switch: set value source	D15A [1]	switch: control function: heating (pos.) / cooling (neg.)	D15A [7]	switch: parameter set: #1 / #2	switch: direction of rotation: cw / ccw	switch: tach out	signal: diagnostics out	signal: fan modulation level %	signal: actual speed	signal: system modulation level															

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-205651-1
Date: 2020-03-17
Housing: 15753-2-4037

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	1680	2150	3.35	78	86	87	25590	0	15060	0.00
2	3~	400	50	1680	2780	4.28	77	85	86	22755	150	13390	0.60
3	3~	400	50	1680	3366	5.15	79	86	87	19525	300	11490	1.20
4	3~	400	50	1680	3800	5.80	87	96	96	15505	420	9125	1.69
5	3~	400	50	1500	1527	2.38	75	83	84	22835	0	13440	0.00
6	3~	400	50	1500	1972	3.04	74	82	83	20290	121	11945	0.49
7	3~	400	50	1500	2391	3.66	76	83	84	17420	240	10255	0.96
8	3~	400	50	1500	2712	4.14	85	93	93	13825	335	8140	1.34
9	3~	400	50	1200	782	1.22	70	77	79	18265	0	10750	0.00
10	3~	400	50	1200	1010	1.55	69	76	77	16235	77	9555	0.31
11	3~	400	50	1200	1224	1.87	71	78	78	13935	153	8200	0.61
12	3~	400	50	1200	1389	2.12	79	87	88	11060	214	6510	0.86
13	3~	400	50	900	330	0.51	63	70	71	13700	0	8065	0.00
14	3~	400	50	900	426	0.66	61	69	70	12175	43	7165	0.17
15	3~	400	50	900	516	0.79	64	70	71	10450	86	6150	0.35
16	3~	400	50	900	586	0.89	72	80	80	8295	120	4885	0.48

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase