

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guide vanes

Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
Phone +86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

Nominal data

Type	W3G800-LU21-03	
Motor	M3G150-IF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1090
Power consumption	W	2650
Current draw	A	4
Max. back pressure	Pa	290
Max. back pressure	in. wg	1.16
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Occasional start-up at temperatures between -40 °C and -25 °C is permitted. For continuous operation at ambient temperatures below -25 °C (such as refrigeration applications), a fan design with special low-temperature bearings must be used.

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	56.4	36.2	09 Power consumption P_{ed}	kW	2.54
02 Measurement category		A		09 Air flow q_v	m³/h	17745
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	275
04 Efficiency grade N		60.2	40	10 Speed (rpm) n	min ⁻¹	1090
05 Variable speed drive		Yes		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$ LU-187913

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guide vanes

Technical description

Weight	46.55 kg
Size	800 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Impeller material	PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Material guide vanes	PP plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Internal diffuser material including cover	PP plastic
Number of blades	5
Blade pitch	0°
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guide vanes


Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; CE
Approval	UL 1004-7 + 60730-1; EAC; CSA C22.2 No. 77 + CAN/CSA-E60730-1

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guide vanes

Product drawing




1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
3	Tightening torque 1.5 ± 0.2 Nm
4	Tightening torque 2 ± 0.3 Nm
5	Attachment holes for FlowGrid 80000-2-2957 (not included in scope of delivery)

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guide vanes

Mounting dimensions




	Diameter of the necessary recess for mounting the fan housing in the end device
	BG630: D = Ø785 mm
	BG710: D = Ø830 mm
	BG800: D = Ø950 mm
	BG910: D = Ø1050 mm

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)

Fan housing with guide vanes

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guide vanes


Terminal/plug assignment

○ configurable option		configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification	CON2	configurable IO mode	OUTPUT																										
○ Din1 (active high): digital input							D158 [0]	○	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D00C [1]	pulse input for auto-addressing	D130 [4]	pulse output for auto-addressing											
○ Ain1 0-10V/PWM: analog input		voltage parameterizable 3.3...24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV	D158 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO1	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [5]	Umax = 50VDC, Imax = 20mA, SELV	D158 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Tach out (open collector output)																																	
○ Diagnostics out (open collector output)																																	
○ Din2 (active high): digital input																																	
○ Ain2 0-10V/PWM: analog input		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO2	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Ain2 4-20mA: analog input																																	
○ Din3 (active high): digital input																																	
○ Din3 (active low): digital input																																	
○ PWMIn3: digital input, idle level high		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO3	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ PWMIn3: digital input, idle level low																																	
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO4	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO5	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO6	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO7	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO8	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO9	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO10	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO11	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO12	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO13	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO14	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	Umax = 50VDC, Imax = 20mA, SELV	D159 [6]	Umax = 50VDC, Imax = 20mA, SELV	D159 [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [2]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [3]	RI = 125R, characteristic curve parameterizable, SELV	D15A [0]	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [1]	D15A [7]	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	0-10V max. 5mA max output frequency 300Hz, SELV	D16E [...]	voltage output	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage
○ Aout3 0-10V: analog output																																	
○ Tacho out (pulses), analog output																																	
○ Diagnostics out (pulses)																																	
○ Diagnostics out (pulses)		15...50VDC	D159 [0]	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	IO15	○	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D																									

EC axial panel fan - AxiBlade

sickle-shaped blades (S series)
Fan housing with guide vanes

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-187913-1
Date: 2017-08-02
Housing: 15863-2-4037

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	1090	1835	2.89	72	80	82	29175	0	17170	0.00
2	3~	400	50	1090	2188	3.41	71	79	80	25800	100	15185	0.40
3	3~	400	50	1090	2454	3.80	74	82	82	21570	200	12695	0.80
4	3~	400	50	1090	2650	4.00	83	91	91	16395	290	9650	1.16
5	3~	400	50	950	1218	1.92	69	76	79	25450	0	14980	0.00
6	3~	400	50	950	1450	2.26	67	75	77	22495	77	13240	0.31
7	3~	400	50	950	1625	2.52	71	78	78	18805	153	11070	0.61
8	3~	400	50	950	1724	2.67	80	87	88	14295	221	8415	0.89
9	3~	400	50	800	727	1.15	64	72	74	21430	0	12615	0.00
10	3~	400	50	800	866	1.35	63	71	72	18945	54	11150	0.22
11	3~	400	50	800	970	1.50	67	74	74	15835	109	9320	0.44
12	3~	400	50	800	1030	1.59	75	83	83	12040	156	7085	0.63
13	3~	400	50	650	390	0.62	59	67	69	17415	0	10250	0.00
14	3~	400	50	650	464	0.72	58	66	67	15390	36	9060	0.14
15	3~	400	50	650	520	0.81	61	69	69	12865	72	7575	0.29
16	3~	400	50	650	552	0.85	70	78	78	9780	103	5755	0.41

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase