





Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	 2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H2O)	(dB(A))	(g)	
PF75301B1-1B000-A99		12	200	2.40	3400	15.5	0.57	42.0	85.0	1
PF75301B2-1B000-A99		12	142	1.71	3000	13.8	0.43	38.6	85.0	2
PF75301B3-1B000-A99		12	82	0.99	2400	10.8	0.24	32.9	85.0	3
PF75302B1-1B000-A99		24	115	2.76	3400	15.5	0.57	42.0	88.0	1
PF75302B2-1B000-A99		24	80	1.92	3000	13.8	0.43	38.6	88.0	2
PF75302B3-1B000-A99		24	47	1.13	2400	10.8	0.24	32.9	88.0	3



97x94x33 mm

22.4~30.5 CFM




■ Specification


Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
PMB1297PYB1-AY (2).GN	☉	12	600	7.20	3600	30.5	0.92	55.8	185.00	1
PMB1297PYB2-AY (2).GN	☉	12	440	5.28	3200	26.6	0.65	53.1	185.00	2
PMB1297PYB3-AY (2).GN	☉	12	300	3.60	2700	22.4	0.43	50.0	185.00	3

■ Function R Type : (2).R.GN / F Type : (2).F.GN

■ Air Flow-Static Pressure Characteristics



■ External dimensions(mm)



97x95x33 mm

44.2~54.7 CFM




■ Specification

Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
PF97331BX-B000-A99	☉	12	3500	42.00	6800	54.7	5.22	63.2	184.0	1
PF97331B1-B000-A99	☉	12	1600	19.20	5400	44.2	3.39	58.0	184.0	2

■ Function R Type : F99 / F Type : G99 / PWM : H99, Q99, S99

■ Air Flow-Static Pressure Characteristics



■ External dimensions(mm)

