

SUNON

SPECIFICATION FOR APPROVAL

FOR REFERENCE

CUSTOMER :

DESCRIPTION : AXIAL AC FAN

DIMENSIONS : 80X80X38 mm

M O D E L : SF23080A

P/N : 2083HBL.GN

SUNON SPEC. NO. : A08000560G-C0

CUSTOMER :

APPROVAL NO.

APPROVED BY :

CUSTOMER

(AUTHORIZED)

DRAWN	Tina	CHECKED	Cindy	APPROVED	Cindy	SPEC.NO	A08000560G-C0
						ISSUE DATE	07.24.2025
						EDITION	0
						REVISION DATE	
						E.SPEC	EA80035

AXIAL AC FAN
MODEL : SF23080A
P/N : 2083HBL.GN

CHARACTERISTICS

- 1. Motor Design** : **Reliable Shaded-Pole Motor Construction.**
- 2. Insulation Resistance** : **500Megohms minimum at 500 VDC.**
- 3. Dielectric Strength** : **1500 VAC for one second .**
- 4. Motor Protection** : **Impedance protected.**
- 5. Noise Level** : **Measured in a semi-anechoic chamber**
with background noise level below 15
dB(A). The fan is running in free air with the
- from the fan intake.**
- 6. Tolerance** : **±15% on rated power and current.**
- 7. Air Performance** : **Measured by a double chamber. The values**
are recorded when the fan speed has stabilized
at rated voltage.

Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

SPEC.NO	A08000560G-C0	REVISION DATE	
ISSUE DATE	07.24.2025	E D I T I O N	0
P A G E	2 O F 10		

SPECIFICATIONS


MODEL: SF23080A**P/N : 2083HBL.GN**

- 1-1. Rated Voltage : 220-240 VAC 50/60 Hz**
- 1-2. Operating Voltage Range : 185-245 VAC**
- 1-3. Starting Voltage : 185 VAC(25 deg. C POWER ON/OFF)**
- 1-4. Rated Speed : 2400/2850 RPM $\pm$ 10%**
- 1-5. Air Delivery : 24/31 CFM**
- 1-6. Static Pressure : 0.13/0.19 Inch-H₂O**
- 1-7. Rated Current : 0.09/0.08 AMP**
- 1-8. Rated Power : 14/13.5 WATTS**
- 1-9. Noise Level : 32/36.5 dB(A)**
- 1-10. Direction of Rotation : Counter-clockwise viewed from front of fan blade**
- 1-11. Operating Temperature : -10 to +70 deg. C**
- 1-12. Storage Temperature : -40 to +70 deg. C**
- 1-13. Bearing System : Precision ball bearing system**
- 1-14. Weight : 340 g**
- 1-15. Safety : UL/CUR/TUV NORD/CE/CCC Approvals**
- 1-16. Protection : ☐Automatic Restart Capability**
Note:The motor will shut down when rotor was locked, then auto restart within 10 seconds.
☐Polarity Protection

NO	A08000560G-C0	REVISION DATE	
DATE	07.24.2025	E D I T I O N	0
P A G E	3 O F 10		

PERFORMANCE CURVES

STATIC
PRESSURE




NO	A08000560G-C0	REVISION DATE	
DATE	07.24.2025	E D I T I O N	0
P A G E	4 OF 10		

MATERIAL

2. Material

- 2-1. Frame
- :
- DIE-CAST ALUMINUM
- 2-2. Impeller
- :
- Thermoplastic PBT of UL 94V-0
- 2-3. Lead Wire
- :
- UL3266, 24 awg, GRAY

DIMENSIONS




Air Flow Direction: Toward label side.

UNIT : mm

NO	A08000560G-C0	REVISION DATE	
DATE	07.24.2025	E D I T I O N	0
P A G E	5 OF 15		

LABEL



(a)Dimension	(b)Model Name	(c)Voltage	(d)Power Consumption	(e)Output Power Consumption
40	SF23080A2083HBL.GN	220-240	18.00/16.00	0.05/0.24

(f)Rated Speed	(g)Frequency	(h)Protection	(i)Protection Class	(j)Safety
2400/2850	50/60	IMPEDANCE PROTECTED	B	CCC/CE/TUV Nord/UL+CUR

1.English Font: Swis721 Series & Switzerland Narrow,Chinses Font: 超研澤中明簡體.

2.Safety(CCC/CE/TUV Nord/UL+CUR)



IO	A08000560G-C0	REVISION DATE	
DATE	07.24.2025	E D I T I O N	0
P A G E	6 O F 10		

Notes

I .SAFETY

1. **DO NOT** use or operate this fan in excess of the limitations set forth in this specification. SUNON is not be responsible for the non-performance of this fan and/or any damages resulting from its use, if it is not used or operated in accordance with the specifications.
 2. **SUNON** recommends adding a protection circuit to the product or application in which this fan is installed, such as a thermo-fuse, or current-fuse or thermo-protector. The failure to use such a device may result in smoke, fire, electric shock by insulation degradation in cases of motor lock, motor lead short circuit, overload, or over voltage, and/or other failure.
 3. **SUNON** recommends installing a protection device to the product or application in which this fan is installed if there is a possibility of reverse-connection between VDC (+) and GND (-). The failure to install such a device may result in smoke, fire, and/or destruction, although these conditions may
- Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com
4. **THIS FAN MUST BE INSTALLED AND USED** in compliance with all applicable safety standards and regulations.
 5. **Use proper care when handling and/or installing this fan.** Improper handling or installation of this fan may cause damage that could result in unsafe conditions.
 6. **Use proper care during installation and/or wiring.** Failure to use proper care may cause damage to certain components of the fan including, but not limited to, the coil and lead wires, which could result in smoke and/or fire.
 7. **DO NOT** use power or ground PWM to control the fan speed. If the fan speed needs to be adjusted, please contact Sunon to customize the product design for your application.
 8. **For critical or extreme environments, including non stop operation, please contact Sunon and we will gladly provide assistance with your product selection to ensure an appropriate cooling product for your application.**

SPEC.NO	A08000560G-C0	REVISION DATE	
ISSUE DATE	07.24.2025	E D I T I O N	0
P A G E	7 OF 10		

Notes

II. SPECIFICATION MODIFICATION

1. **SUNON offers engineering assistance on fan installation and cooling system design.**
2. **All changes, modifications and/or revisions to the specifications, if any, are incorporated in the attached specifications.**
3. **No changes, modifications and/or revisions to these specifications are effective absent agreement, by both Sunon and the customer, in writing.**
4. **This fan will be shipped in accordance with the attached specification unless SUNON and the customer have agreed otherwise, in writing, as specified in Paragraph 3, above.**

III. OTHER

1. **When building your device, please examine thoroughly any variation of EMC, temperature rise, life data, quality, etc. of this product by shock/drop/vibration testing, etc. If there are any problems or accidents in connection with this product, it should be mutually discussed and examined.**
2. **Use proper care when handling this fan. Components such as fan holders or bearings may be damaged, if touched with fingers or other objects. Additionally, static electricity (ESD) may damage the internal circuits of the fan.**
3. **DO NOT operate this fan in proximity to hazardous materials such as organic silicon, cyanogens, formalin, phenol, or corrosive gas environments including, but not limited to, H₂S, SO₂, NO₂, or Cl₂.**
4. **SUNON recommends that you protect this fan from exposure to outside elements such as dust, condensation, humidity or insects. Exposure of this fan to outside elements such as dust, condensation, humidity or insects may affect its performance and may cause safety hazards. SUNON does not warrant against damage to the product caused by outside elements.**
Re: The term can be excluded, if the fan has been with IP design and meets customer's IP requirement.

IO	A08000560G-C0	REVISION DATE	
DATE	07.24.2025	E D I T I O N	0
P A G E	8 OF 10		

Notes

5. This fan must be installed properly and securely. Improper mounting may cause harsh resonance, vibration, and noise.
6. Fan guards may prevent injury during handling or installation of the fan and are available for sale with this fan.
7. Unless otherwise noted, all testing of this fan is conducted at 25°C ambient temperature and sixty-five percent (65%) relative humidity.
8. DO NOT store this fan in an environment with high humidity. This fan must be stored in accordance with the attached specifications regarding storage temperature. If this fan is stored for more than 6 months, SUNON recommends functional testing before using.
9. SUNON reserves the right to use components from multiple sources at its discretion. The use of components from other sources will not affect the specifications as described herein.
10. The “Life Expectancy” of this fan has not been evaluated for use in combination with any end application. Therefore, the Life Expectancy Test Reports (L10 and MTTF Report) that relate to this fan are only for reference.

VI. WARRANTY

This fan is warranted against all defects which are proved to be fault in our workmanship and material for one year from the date of our delivery. The sole responsibility under the warranty shall be limited to the repair of the fan or the replacement thereof, at SUNON’s sole discretion. SUNON will not be responsible for the failures of its fans due to improper handing, misuse or the failure to follow specifications or instructions for use. In the event of warranty claim, the customer

customer’s equipment as a result of any fans

Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

PROVEN TO BE DEFECTIVE

	SPEC.NO	A08000560G-C0	REVISION DATE	
	ISSUE DATE	07.24.2025	E D I T I O N	0
	P A G E	9 O F 10		

SUNON

Declaration of RoHS

Beijing Hengrui Mechanical and Electrical Equipment Co.,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

SUNON Electronics (Beihai) Co.,Ltd., Lizhun
SUNON Electronics (Beihai) Co., Ltd. and SUNON Electronics (Philippines) Co., Ltd.)
guarantee that the products made by SUNON comply with the requirements of the
Restriction of Hazardous Substances in Electrical and Electronic Equipment
(RoHS) Directive (EU) 2015/863 amending 2011/65/EU the Annex II , the use of the
restricted substances in homogeneous materials is in accordance with the following
limit values:

No	Substance	Limit Value
1	Cadmium (Cd)	<100 ppm
2	Hexavalent Chromium (CrVI)	<1000 ppm
3	Lead (Pb) *	<1000 ppm
4	Mercury (Hg)	<1000 ppm
5	Polybrominated Biphenyls(PBBs)	<1000 ppm
6	Polybrominateddiphenyl ethers (PBDEs)	<1000 ppm
7	Di-butyl Phthalate(DBP)	<1000 ppm
8	Benzyl butyl Phthalate(BBP)	<1000 ppm
9	Di-ethylhexyl Phthalate (DEHP)	<1000 ppm
10	Di-isobutyl Phthalate (DIBP)	<1000 ppm

* Note: Lead content in homogeneous materials may be greater than 1000 ppm, such as steel alloys, copper alloys, high melting point solder, and ceramics and glass, which applies to exemption 6(a), 6(c), 7(a) and 7(c)-I respectively.

*This product complies with the RoHS and REACH Compliance Statement published on

SPEC.NO	A08000560G-C0	REVISION DATE	
ISSUE DATE	07.24.2025	E D I T I O N	0
P A G E	10 OF 10		