

60x60x20 mm

14.1~23.0 CFM




■ Specification


Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
EE60201B1-000U-999	☼	12	135	1.62	4500	23.0	0.18	34.5	52.0	1
EE60201B2-000U-999	☼	12	95	1.14	3700	19.0	0.14	29.0	52.0	2
EE60201B3-000U-999	☼	12	70	0.84	3000	14.1	0.09	24.5	52.0	3
EF60202B1-000U-A99	☼	24	60	1.44	4500	23.0	0.18	34.5	52.0	1
EF60202B2-000U-A99	☼	24	38	0.92	3700	19.0	0.14	29.0	52.0	2
EF60202B3-000U-A99	☼	24	23	0.56	3000	14.1	0.09	24.5	52.0	3

■ Function (12V) Auto Restart : A99 / F Type : C99, G99
(24V) R Type : F99 / F Type : G99

■ Air Flow-Static Pressure Characteristics



■ External Dimensions(mm)



※ All model could be customized. Please contact with Sunon Sales.

※ Specifications are subject to change without notice. Please Visit SUNON website at www.sunon.com for update information.